## <u>CLAIMS</u>

## What is claimed is:

- 1 1. A system for organizing one or more elongated objects, each elongated object
- 2 having a length and a width, the length exceeding the width, comprising:
- a first fastener adapted to extend for a distance along the length of at least a first
- 4 one of the elongated objects and capable of coupling the first one of the elongated objects
- 5 to a second one of the elongated objects or to another object.
- 1 2. The system of claim 1, wherein the first fastener is adapted to extend along
- 2 substantially all of the length of at least the first one of the elongated objects.
- 1 3. The system of claim 1, wherein the first fastener is reusable.
- 1 4. The system of claim 1, wherein the first fastener comprises at least one male
- 2 component integrated with the first one of the elongated objects.
- 1 5. The system of claim 4, wherein the first fastener comprises at least one raised
- 2 bead.
- 1 6. The system of claim 1, wherein the first fastener comprises at least one female
- 2 component integrated with the first one of the elongated objects.
- 1 7. The system of claim 6, wherein the first fastener comprises at least one indented
- 2 channel defined in the first one of the elongated objects.
- 1 8. The system of claim 1, wherein the first fastener comprises an adhesive substance.
- 1 9. The system of claim 1, wherein the first fastener comprises a wrap adapted to be
- 2 applied around the first one of the elongated objects, the wrap comprising an outer

- 3 surface facing away from the first one of the elongated objects and an inner surface
- 4 facing towards the first one of the elongated objects.
- 1 10. The system of claim 9, wherein a channel is defined in the inner surface of the
- 2 wrap for receiving the first one of the elongated objects.
- 1 11. The system of claim 10, wherein the first one of the elongated objects is
- 2 removable from the wrap.
- 1 12. The system of claim 10, wherein a cut extending lengthwise along the wrap is
- defined in the wrap, the cut extending from the outer surface of the wrap to the inner
- 3 surface of the wrap.
- 1 13. The system of claim 10, wherein at least one channel is defined in the outer
- 2 surface of the wrap for receiving the second one of the elongated objects.
- 1 14. The system of claim 1, further comprising a second fastener adapted to extend for
- 2 a distance along the length of at least the second one of the elongated objects and capable
- 3 of coupling the second one of the elongated objects to the first one of the elongated
- 4 objects, wherein the first fastener and the second fastener are capable of mating together
- 5 to couple the first one of the elongated objects and the second one of the elongated
- 6 objects together.
- 1 15. The system of claim 14, wherein the first fastener comprises at least one male
- 2 component integrated with the first one of the elongated objects, and the second fastener
- 3 comprises at least one female component integrated with the second one of the elongated
- 4 objects.
- 1 16. The system of claim 1, further comprising a converter adapted for attachment to
- 2 the first fastener.

- 1 17. The system of claim 16, wherein the converter comprises a plurality of female
- 2 components, and wherein at least one female component is adapted for attachment to the
- 3 first fastener.
- 1 18. The system of claim 17, wherein the converter comprises a plurality of indented
- 2 channels, and wherein at least one indented channel is adapted for attachment to the first
- 3 fastener.
- 1 19. The system of claim 16, wherein the converter comprises a plurality of male
- 2 components, and wherein at least one male component is adapted for attachment to the
- 3 first fastener.
- 1 20. The system of claim 19, wherein the converter comprises a plurality of raised
- 2 beads, and wherein at least one raised bead is adapted for attachment to the first fastener.
- 1 21. The system of claim 16, wherein the converter comprises a hanger having a
- 2 second fastener adapted for attachment to the first fastener.